

Job Name: _____	Client Name: _____
Job Location - City: _____	State: _____
Product: _____	Quote: _____

Created By: _____	Date: _____
Customer Approval: _____	Date: _____

CARBON STEEL - POWDER

SPECIFICATIONS

Product Application - Steel structures, steel components and aluminum accessories purchased with steel structures. Use this system as an economical option for basic performance of paint.

Warranty - 1 year adhesion/corrosion

Surface Preparation - The exterior steel surface is blast cleaned to Steel Structures Painting Council Surface Preparation Specification No. 6 (SSPC-SP6) requirements utilizing cast steel abrasives conforming to the Society of Automotive Engineers (SAE) Recommended Practice J827. The blast method used is a recirculating, closed cycle centrifugal wheel system with abrasive conforming to SAE Shot Number S280.

Interior Coating - Interior surfaces (pole shafts only) at the base end for a length of approximately 2.0' are coated with the same coating used on the exterior. The coating is electrostatically applied and cured in a gas fired convection oven.

Exterior Coating - TGIC or Urethane Polyester Powder. Urethanes and TGIC polyesters are both exterior durable powders and have good gloss and color retention. They can be used in a one coat application over most metal substrates in a mild to moderate environment. They offer good scratch and abrasion resistance.

All exterior surfaces are coated to an average dry film thickness (DFT) of 4.0 mils. The coating is electrostatically applied and cured in a gas fired convection oven. The thermosetting powder resin provides adhesion that meets 5A or 5B classifications of ASTM D3359.

The Finish Painted system is available in 11 standard colors that match the most commonly used colors in the industry. There are thousands of other colors available upon request.

Standard colors available:

- Black (BK)
- Dark Bronze (DB)
- Medium Bronze (MB)
- White (WH)
- Light Gray (LG)
- Bronze (CB)
- Dark Green (DG)
- Sandstone (ST)
- Hunter Green (HG)
- Slate Gray (SG)
- Silver (SL)

