

901191-10 and 901191-50



SPECIFICATIONS

General	The PIM Shield Threaded Rod Insulator is a low PIM solution for mounting stainless steel or galvanized steel 3/8" threaded hardware to 0.75-inch diameter snap-in hanger mounting holes.
Mounting	Insert insulator halves into each side of mounting hole and install threaded hardware (sold separately). The protruding features on each insulator align the two halves and prevent the threaded rod from contacting the mounting hole.
Mounting hole diameter	0.70-inch to 0.76-inch diameter
Mounting bar thickness	0.115-inch to 0.375-inch
System PIM performance (when tested at next higher assembly)	IM3 < -100 dBm when tested in accordance with IEC 62037-8, near field test, 2x 20W test tones, while subjected to dynamic stimulus
Material	33% Glass Filled Nylon
Plastic Base Color	Black
Operating temperature	-40°C to +70°C

PACKAGING DETAILS

	901191-10	901191-50
Qty Per Package	Qty 10 (20 halves)	Qty 50 (100 halves)
Case Dimensions	12.2-inch x 6.2-inch x 4.5-inch	12.0-inch x 15.0-inch x 8.0-inch
Case Weight	1.5 lbs.	7.0 lbs.
Quantity per case	10 kits of 10	10 kits of 50

